





This new generation portable beveling machine BM-21 is one of the best tools for machining plates and pipes prior to welding. It is a beveller developed on the basis of many years of experience with highly successful predecessor model BM-20, which for many years was on the most favored tool list for many customers worldwide.



Most important features include:

- new single milling head equipped with 10 square inserts, that makes machining process far more efficient with little operator's effort
- fast and easy exchange of inserts with no need for special adjustment
- extended working range from 0 to 60 degrees with continuous angle adjustment
- · easy setting of bevel angle and bevel width
- vibration insulation protects both the operator and electronics against vibration
- one universal guide plate for beveling both plates and pipes replaces 3 different attachments used with BM-20

Special model BM-21S with lower speed motor dedicated for machining STAINLESS STEELS is now available





Max. bevel width 21 mm



0-609

To





Facing off



Pipe beveling OD 150-300mm OD 260-600mm (option)

BM-21 TECHNICAL SPECIFICATION	
Power supply	230VAC/50Hz or 115 VAC/60 Hz
Induction motor	with increased start-up current
Power	1100 W
	BM-21S: 1600 W (for 50 Hz); 1800 W (for 60 Hz)
Spindle speed	2820 rpm
	BM-21S: 1360-1630 rpm (at 230 V) and 1300-1560 rpm (at 115 V)
Tooling	integrated milling head with 10 square TCT inserts
Beveling angle	0-60° with continuous angle adjustment
Max bevel width	21 mm
Weight	20 kg (43 lbs)
	BM-21S: 23 kg (51 lbs)







Plate facing-off Plate beveling Pipe beveling



Mono block milling head, with 10 indexable inserts fixed with screws.



37% reduced vibration

BM-21 contains anti-vibration system including special shaped gripping construction with 4 dampers, enabling more comfortable operation, minimizing unwanted vibrations.

According to manufacturer's research the new anti-vibration system reduces vibration perceptibility by 37%.

Standard universal guide plate for beveling both plates and pipes Ø 150-300mm (6-12")



Continuous angle adjustment from 0 to 60 degrees.





Optional guide for pipes Ø 260-600mm (10-24") Product code: PRW-0461-22-00-00-0





Your local dealer: